

NP12-20Ah 12V20Ah


Valve Regulated Lead Acid Battery




Specifications

| | | |
|-----------------------|------------------------|--------------------|
| Nominal voltage | 12V (6 cells per unit) | |
| Rated capacity (20HR) | 20Ah/10.5V | |
| Dimensions | Length | 181±2mm (7.13inch) |
| | Width | 77±1mm (3.03inch) |
| | Height | 167±2mm (6.57inch) |
| | Total height | 167±2mm (6.57inch) |
| Approx. weight | 5.50kg (12.10lbs)±4% | |

Outer dimensions (mm)



Terminal type (mm)



Characteristics

| | | |
|---|---|--|
| Capacity (25°C) | 20HR (10.5V) | 20Ah |
| | 10HR (10.5V) | 18.5Ah |
| | 1HR (9.60V) | 12Ah |
| Terminal type | | T3/T12 |
| Internal resistance (Fully charged, 25°C) | | Approx. 12mΩ |
| Capacity affected by temperature (10HR) | 40°C | 102% |
| | 25°C | 100% |
| | 0°C | 85% |
| | -15°C | 65% |
| Self-discharge (25°C) | 3 months | Remaining capacity: 91% |
| | 6 months | Remaining capacity: 82% |
| | 12 months | Remaining capacity: 65% |
| Nominal operating temperature | | 25°C±3°C (77°F±5°F) |
| Operating temperature range | Discharge | -15°C~50°C (5°F~122°F) |
| | Charge | -10°C~50°C (14°F~122°F) |
| | Storage | -20°C~50°C (-4°F~122°F) |
| Float charging voltage (25°C) | | 13.60 to 13.80V Temperature compensation: -18mV/°C/Block |
| Cyclic charging voltage (25°C) | | 14.50 to 15.00V Temperature compensation: -30mV/°C/Block |
| Maximum charging current | | 6A |
| Maximum discharge current | | 300A (5 sec.) |
| Design life | 5 years for floating (25°C) | |
| | Eurobat (20°C): 3-5 years, standard commercial. | |

Construction

| Component | Positive plate | Negative plate | Container | Cover | Separator | Electrolyte | Safety valve | Terminal |
|--------------|----------------|----------------|-----------|-------|-----------|---------------|--------------|----------|
| Raw material | Lead dioxide | Lead | ABS | ABS | AGM | Sulfuric acid | Rubber | Copper |

Constant current discharge characteristics unit: Ampere/Block (at 25°C, 77°F)


| F.V/Time | 5min | 10min | 15min | 30min | 60min | 2h | 3h | 4h | 5h | 10h | 20h |
|----------|------|-------|-------|-------|-------|------|------|------|------|------|------|
| 9.60V | 76.4 | 48.4 | 37.8 | 21.3 | 13.1 | 7.17 | 4.96 | 4.10 | 3.49 | 1.89 | 1.02 |
| 9.90V | 74.1 | 46.9 | 36.9 | 20.9 | 12.9 | 7.12 | 4.93 | 4.08 | 3.47 | 1.89 | 1.01 |
| 10.2V | 71.1 | 45.0 | 35.5 | 20.2 | 12.6 | 7.06 | 4.89 | 4.05 | 3.44 | 1.88 | 1.01 |
| 10.5V | 68.0 | 43.1 | 34.3 | 19.7 | 12.3 | 6.95 | 4.86 | 4.02 | 3.42 | 1.87 | 1.00 |
| 10.8V | 64.2 | 40.7 | 32.5 | 19.0 | 11.9 | 6.78 | 4.71 | 3.90 | 3.32 | 1.83 | 0.98 |

Constant power discharge characteristics unit: Watt/Block (at 25°C, 77°F)


| F.V/Time | 5min | 10min | 15min | 30min | 60min | 2h | 3h | 4h | 5h | 10h | 20h |
|----------|------|-------|-------|-------|-------|------|------|------|------|------|------|
| 9.60V | 853 | 546 | 431 | 244 | 152 | 83.8 | 58.9 | 48.8 | 41.7 | 22.7 | 12.2 |
| 9.90V | 827 | 530 | 421 | 239 | 149 | 83.3 | 58.5 | 48.5 | 41.4 | 22.6 | 12.1 |
| 10.2V | 793 | 508 | 405 | 232 | 146 | 82.6 | 58.1 | 48.2 | 41.1 | 22.5 | 12.1 |
| 10.5V | 759 | 486 | 391 | 226 | 143 | 81.4 | 57.7 | 47.9 | 40.8 | 22.4 | 12.0 |
| 10.8V | 716 | 459 | 371 | 218 | 138 | 79.3 | 56.0 | 46.4 | 39.6 | 21.9 | 11.8 |

Note 1: Above characteristics data can be obtained within three charge and discharge cycles.


● Discharge characteristics (25°C)




● Charging characteristics (25°C)




● Temperature effects on capacity




● Self-discharge characteristics




● Floating life on temperature



● Cycle life on D.O.D (25°C)



● Relationship for OCV and capacity (25°C)



● Relationship for charging voltage and temperature

